



✘ Coleman brands: Signal, Polar/Solar, _ _ .

✘ Multi-Pair Cables, Individually Shielded Pairs

Control cable for power limited circuits. Processing equipment, audio, and other low voltage control uses requiring cable with excellent electrical characteristics.

Conductors: Stranded Tinned Copper
Insulation: Polypropylene
Construction: Individually shielded pairs cabled together on common axis to reduce cable diameter
Shield: Aluminum Mylar shield over each pair with stranded tinned copper drain wire
Jacket: PVC
Temperature Rating: 60°C
Operating Voltage: 300V
Approvals: UL Type CM/CI2
 NEC Article 800/725



Part No.	AWG	No.of Cond.	Copper Stranding	Drain Wire AWG	Nom. Insulation Thick.	Jacket Thick.	Nom. O.D.	Color Code	Nom. Cap. Pf/Ft. ^ **	Weight per 1000'
22 AWG										
642202	22	4 Conductors, 2 Pairs Twisted	7x30	24 AWG	.008	.025	.170	Pair 1 Black/Red Pair 2 Green/White	29 53	21

^ Conductor to conductor
 ** Conductor to shield

[\[Start Page\]](#) [\[Corporate\]](#) [\[Catalog\]](#) [\[New Products\]](#) [\[Technical\]](#) [\[News\]](#) [\[Employment\]](#) [\[Contact Us\]](#)

✘ footersymbol.gif (1705 bytes)

footerright