

### Product type designation

Product description

### IE FC RJ45 Plug 180 (4x2)

RJ45 data connector

IE FC RJ45 PLUG 180 4X2, RJ45 CONNECTOR

(10/100/1000MBIT/S) WITH ROBUST METAL HOUSING FC

CONNECTING METHOD, FOR IE FC CABLE 4X2 (AWG24) 180

DGR OUTGOING CABLE 1 PACKAGE = 1 PIECE



### Suitability for use

For connection to IE FC TP cables 4x2, suitable for fast assembly with the FastConnect system

### Transmission rate

Transfer rate / for Industrial Ethernet

10 Mbit/s, 100 Mbit/s, 1000 Mbit/s

### Interfaces

Number of electrical connections

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

8

1

Type of electrical connection

- for Industrial Ethernet FC TP cables
- for network components or terminal equipment

integrated cut-and-clamp contacts for 8-wire TP FC installation cable

RJ45 connector

Type of electrical connection / FastConnect

Yes

### Mechanical data

Material / of the enclosure

metal

Number of reuses

10

### Design, dimensions and weight

Type of cable outlet

180° cable outlet

Width

13.7 mm

Height

16 mm

Depth

55 mm

Net weight

35 g

## Permitted ambient conditions

|  |                |
|--|----------------|
| Ambient temperature  |                |
| • during operation   | -40 ... +85 °C |
| • during storage   | -40 ... +85 °C |
| • during transport   | -40 ... +85 °C |
| Relative humidity / at 25 °C / without condensation / during operation / maximum | 95 %           |
| Protection class IP  | IP20           |

## Product properties, functions, components / general

|                   |     |
|-------------------|-----|
| Product property  |     |
| • PoE capability  | Yes |
| • PoE+capability  | Yes |
| • silicon-free    | Yes |
| Product component |     |
| • strain relief   | Yes |

## Standards, specifications, approvals

|   |      |
|---|------|
| Certificate of suitability                        |      |
| • RoHS conformity                                 | Yes  |
| • UL approval                                     | Yes  |
| • cULus approval                                  | Yes  |
| • Railway application in accordance with EN 50155 | No   |
| Standard for structured cabling                   | Cat6 |

## Further Information / Internet Links

|   |   |
|---|---|
| Internet-Link                                     |   |
| • to website: Selector SIMATIC NET SELECTION TOOL | <a href="http://www.siemens.com/snst">http://www.siemens.com/snst</a>                                     |
| • to website: Industrial communication            | <a href="http://www.siemens.com/simatic-net">http://www.siemens.com/simatic-net</a>                       |
| • to website: Industry Mall                       | <a href="https://mall.industry.siemens.com">https://mall.industry.siemens.com</a>                         |
| • to website: Information and Download Center     | <a href="http://www.siemens.com/automation/net/catalog">http://www.siemens.com/automation/net/catalog</a> |
| • to website: Image database                      | <a href="http://automation.siemens.com/bilddb">http://automation.siemens.com/bilddb</a>                   |
| • to website: CAx Download Manager                | <a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                       |
| • to website: Industry Online Support             | <a href="https://support.industry.siemens.com">https://support.industry.siemens.com</a>                   |
| <b>last modified:</b>                             | 24.04.2015  |