

Axial Leaded



1000V - FA HRC Fuses

6Ø X 46 mm

Very Fast Acting Ceramic Sand Filled Fuses

Cartridge



Approvals

UL Recognized (File E76491) 0.1A ~ 1.0A

Interrupting Ratings

0.1A ~ 1.0A 30,000A at 1000VAC

Physical Specification

Materials

Ceramic body / Nickel Plated Brass Caps

Lead Wire:

Diameter Ø0.8 mm 12A and less.

Packaging

Bulk: 10 pcs/box

Tape & Reel: - 1500 pcs/reel

Cartridge Reference Number	Axial Lead Reference Number	Ampere Rating, Amp	Breaking Capacity	Voltage Rating	Pre-Arcing I ² t, A ² s	Total Clearing I ² t, A ² s
G076458	W209733	0,1	200kA cos Φ ≥ 0.2	1000V	0,0002	s
H076459	X209734	0,125			0,0006	0,001
J076460	Y209735	0,16			0,0014	0,003
K076461	Z209736	0,2			0,0022	0,006
L076462	A209737	0,25			0,004	0,01
M076463	B209738	0,315			0,008	0,02
N076464	C209739	0,4			0,017	0,04
P076465	D209740	0,5			0,036	0,08
Q076466	E209741	0,63			0,59	0,16
R076467	F209742	0,8			0,11	0,35
P075660	V209617	1	0,23	0,6		

Time-current characteristics

1000V FA 6x46

