

*ROHS COMPLIANT



BOURNS®

Features

- No backlash
- Compact - requires minimal panel space (22.2 mm diameter requirement)
- For use with precision potentiometers or other rotating devices, up to 15 turns
- Designed for metal shaft
- High Force "Click Brake"
- Available in two versions - black on satin chrome background or white on black background
- RoHS compliant*

H-22 Turns-Counting Dial

Mechanical and Physical Characteristics


Number of Turns	0 to 15
Dial Divisions	50 per turn
Readability - Over 10 Turns.....	2 parts in 1000
Torque With Brake Engaged	6.95 oz.-in. (500 g-cm) minimum
Markings.....	Black on satin chrome background or white on black background
Locking Brake.....	Yes
Weight.....	15 grams (0.53 oz.)
Set Screw	UNC N2-56, one included
Set Screw Tightening Torque	16.94 N-cm (1.5 lbs.-in.) minimum
Hex Key Size	0.05 in. hex

Shaft and Bushing Requirements


Shaft Diameter Requirements	Refer to chart below
Shaft Extension Beyond Panel	18.1 mm (0.712 in.) minimum
	22.2 mm (0.875 in.) maximum
Bushing Extension Beyond Panel	9.53 mm (0.375 in.) maximum

H-22 MOUNTING INSTRUCTIONS

1. Insert potentiometer in panel.
2. Install anti-rotation device using hardware supplied with potentiometer.
3. Turn potentiometer shaft counterclockwise to minimum resistance or voltage ratio.
4. Set the dial to "0.0" and brake on.
5. Insert the dial on the potentiometer shaft lightly against the panel.
6. Tighten set screw to potentiometer shaft.



DIMENSIONS: $\frac{MM}{(IN.)}$



How To Order

Part Number	Accepts Shaft Diameter	Finish
H-22-6A	6.35 mm (.250)	Satin chrome
H-22-6M	6 mm (.236)	Satin chrome
H-22-3A	3.17 mm (.124)	Satin chrome
H-22-6A-B	6.35 mm (.250)	All black

REV. 04/07

*RoHS Directive 2002/95/EC Jan 27 2003 including Annex. Specifications are subject to change without notice. Customers should verify actual device performance in their specific applications.